

**NEW**

**CONSEW** Since 1898

# Model 5457RB-7DD-DSM


## ZIG-ZAG / DECORATIVE STITCHING / DIRECT-DRIVE

*Energy saving ZigZag machine that makes Beautiful Stitches*

- With
- Electronic control
  - Auto Reverse
  - Auto Needle Position
  - Mini Self Oiling System
  - Energy Saving Servo System
  - Large Capacity for Sewing Patterns
  - Rotary Takeup
  - Auto trimmer
  - Adoptive Feed



Titanium coated Hook



Servo Motor Control



Outstandingly Beautiful Stitches

**HIGH-SPEED  
DIRECT-DRIVE  
COMPUTERIZED**

**ZIG-ZAG MACHINE**

# Model 5457RB-7DD-DSM

## APPLICATIONS

- Decorative Zig-Zag stitching on thin, medium and thick fabrics.
- For lingerie, womens jackets, collars attaching lace, elastic band, bottom hemming, edge stitching, butted seaming, applique and similar operations

## FEATURES

- Direct Drive servo motor system dramatically improves efficiency
- Servo motor controlled feed dog interacts with the digital system and stitch counter to create decorative stitches
- Mini oil lubrication system, ensures clean, smooth sewing.
- Multi-function color LCD touch screen operating panel.
- Capable of continuous cycle sewing.
- Expandable feed dog height and wide range of tilt adjustment.
- Feed dog can be adjusted range from upward, horizontal, downward, and adapt to high and low segment sewing function.
- Titanium coated inner hook runs cooler and smoother.
- Special new Feed Design is suitable for a variety of fabrics and efficiently sewing complex patterns.
- Hook axis compensation system which assures that the phase position of the hook tip is always in optimum position.
- Microprocessor control and multiple stitch patterns.
- Combination zig-zag and straight stitcher
- Reverse feed and adjustable reverse stitch length

Patterns	Scallops				Blind stitch									
	Straight stitch	Standard zigzag	2 steps zigzag	3 steps zigzag	Scallop (left)	Scallop (right)	Blind stitch (left)	Blind stitch (right)						
					1	2	3	4	1	2	3	4	Standard type	L-type
Pattern														
Stitch number	-	24	4	6	24	12	24	24	24	12	24	24	Straight line: max. 99 stitches	

**16 basic patterns, such as straight stitch, two and three scallops, blind stitch and L-type stitch. Internally installed zigzag pattern input function, it also provides L-type blind stitch.**

## SPECIFICATIONS

Speed, Max. (S.P.M.)*	4500	Stitch Length, Max.	5 s.p.i. (5 mm)	
Footlift	by Hand	15/64" (6 mm)	Needle	DP x 5
	by Knee	7/32" (5.5 mm)	Stitch Width Max.	11/32" (9 mm)
	Auto footlifter - Optional		Workspace	11-13/16" (300 mm)
Needle Bar Stroke	1 6/25" (31.5 mm)	Weight	165 lbs (75 kg)	

\* Speed depends on width of zig-zag, material and thread.

Specifications subject to change without notice.

©2020 Consew USA -0520