



**U.S. BLINDSTITCH
MACHINE COMPANY**

**A DIVISION OF THE
CONSEW GROUP
OF COMPANIES**

**Model
1118-4**

1118-4

Blindstitch Machine
Single Thread -
Chainstitch



with
Skip And Non-skip Stitch Lever
Swing Down, Narrow Cylinder Arm
Adjustable Thread Tension
1 To 1 Non-skip Stitch And
2 To 1 Skip Stitch

U.S. BLINDSTITCH MACHINE CO.

400 Veterans Blvd., Carlstadt, NJ 07072

Tel: 201-809-2009 • 1-800-225-2852 • FAX: 201-861-9201

www.USBlindstitch.com



U.S. BLINDSTITCH MACHINE COMPANY

A DIVISION OF THE
CONSEW GROUP
OF COMPANIES

Model 1118-4

1118-4

Features:

Stitch length adjustment by push button

Stitch depth penetration adjustment dials

Swing down, narrow cylinder arm allows for easy insertion and removal of work piece

Easy open, swing away work plate for extended working space

Stitch length max: 2-1/2" (3 mm - 9 mm) s.p.i.

Needle: 251 LG

Looper: 2200

Cylinder diameter: 2-1/4" (57 mm)

Work space: 7" (180 mm)

Work plate dimensions: 361 mm x 153 mm

Stitch type: 103

Applications:

Perfect for sewing all weights of materials including synthetics, woolens, cottons, fabric and knits.

1 to 1 non-skip stitches, typical operations include felling edge tapes, bottoms of trousers, cuffs, wiggling in sleeves, facings to canvas and knit goods, turned-up bottoms of fully lined coats, padding collars and lapels, and reinforcing seats.

2 to 1 skip stitch for hemming dresses, skirts, slacks, trousers, sportswear, ladies coats, draperies, blouses and other articles.

Suitable for felling operations requiring a skip stitch to simulate hand-stitching.

2 to 1 skip stitch is recommended for synthetics and other lightweight materials and 1 to 1 for heavier cotton, woolen and linen goods.

**Available Option:
Clinton Industries
attachment for
automated
thread cutting**



**U.S.
BLINDSTITCH
MACHINE CO.**

400 Veterans Blvd.,
Carlstadt, NJ 07072

Tel: 201-809-2009
1-800-225-2852
FAX: 201-861-9201
www.USBlindstitch.com