

# **Model 199R SERIES**

**Regular Bobbin: 199R-1A-1/199R-2A-1/199R-3A-1** 

Large Bobbin: 199RB-1A-1/199RB-2A-1/199RB-3A-1

Long Arm/Large Bobbin: 199RBL-30-1A-1/199RBL-30-2A-1/199RBL-30-3A-1

With

HORIZONTAL AXIS TRANSVERSE ROTARY HOOK
REVERSE FEED
COMBINATION ZIG-ZAG AND STRAIGHT STITCHER







199RBL-30-1A-1 Special order (1A, 2A, 3A) Long arm with 30" work space SINGLE NEEDLE DROP FEED ZIG-ZAG

LOCKSTITCH MACHINES

Interchangeable between 1A, 2A, 3A Stitches by changing gears and cams. (Comes with one set, other sets optional)



## Regular Bobbin: 199R-1A-1/199R-2A-1/199R-3A-1 Large Bobbin: 199RB-1A-1/199RB-2A-1/199RB-3A-1

Long Arm/Large Bobbin: 199RBL-30-1A-1/199RBL-30-2A-1/199RBL-30-3A-1

#### **APPLICATIONS**

199R-1A-1 - used for a wide range of products and operations such as edge sewing, patch sewing, attaching and abutting work, applique work and binding on such materials as leather, vinyl, canvas, cloth, lace and similar materials - Federal stitch 304

199R-2A-1 - three step/two stitch zig-zag Federal stitch 308

- For sewing elastic and other stretch materials, as well as for ornamental stitching
- For stitching such products as boat and truck covers, tents, awnings, sails, parachutes, tarpaulins, canvas bags also many items of military and naval equipment
- Used on such materials as canvas, nylon, vinyl, leather, synthetics and similar materials
- Especially desirable where reinforced stitch is necessary

Also available with special fittings for rope tacking operations

• Used for rope tacking, making loops in rope and attaching small and medium size ropes to such products as truck covers, tents, sails, hammocks, parachutes, grain bags and many items of military and naval equipment

199R-3A-1 - four step/three stitch zig-zag


 Performs similar operations as Model 199R-2A-1 with the added advantage of making an additional stitch for extra reinforcement

#### **FEATURES**

- Horizontal axis transverse rotary hook
- Maximum width of zig-zag : 3/8" (9.5 mm)
- Straight stitcher when zig-zag is set to 'O' mm
- Long arm with 10" free space between needle and arm (all 18-7/8" bed models)
- Locking zig-zag width regulator
- Reverse stitching
- Special fittings available on model 199R-2A-1 for rope end and rope loop stitching
- Model 199RB- with large bobbin and horizontal axis transverse rotary hook
- Model 199RBL-USA Long Arm (up to 30" can be ordered)
- Optional: Interchangeable between 1A, 2A & 3A stitches; Additional parts required (not included).









Optionally available from Clinton Industries: Automatic Footlift and Automatic Backtack





FOOTLIFT

BACKTACK

### **SPECIFICATIONS**

Speed, Max. (S.P.M.) *						
	199R-1A-1 199R-2A-1	199R-3A-1	}	Zig-Zag Stitch	3000 2700	
	199R-1A-1 199R-2A-1	199R-3A-1	}	Straight Stitch	3200 3000	
	199RB/199RBL Series			Zig-Zag/Straight		
Clearance Under Foot			1	<sup>5</sup> /64" (6 mm)		
Needle Bar Stroke			1 <sup>11</sup> /32" (34 mm)			
Stitch Length, Max.			5 spi (5 mm)			

<sup>\*</sup> Speed depends on width of zig-zag, material and thread.

		199R	199RB / RBL			
Needle	16 X 95		135 x 17			
Metal		B75	199RB 199RBL 2120304-312			
Bobbin	Pre-Wound	L	199RB M 199RBL			
Hook		B-70	199RB B79 199RBL			
Bed Size	199R 199RBL-30		18 <sup>7</sup> /8" (178 x 480 mm) 33 <sup>1</sup> /4" (178 x 848 mm)			
Work- Space 10" (258 mm)			199RBL-30 30" (765 mm)			
Z-Z Stitch Width Max. 3/8" (9.5 mm) All Models						