

CONSEW Since 1898

Model 205RB-1

Also available:
205RBATCL(N) Full Auto Function

WITH

REVERSE FEED

LARGE HORIZONTAL AXIS ROTARY HOOK AND BOBBIN

SEMI-AUTOMATIC LUBRICATION with OIL PUMP

**LARGE
BOBBIN**



SINGLE NEEDLE
DROP FEED
ALTERNATING PRESSER FEET
LOCKSTITCH MACHINE

APPLICATIONS

- For sewing medium to medium-heavy weight materials such as cloth, synthetics, vinyl, canvas, leather and various coated and laminated materials
- Suitable for stitching operations on such products as leather coats, jackets, gloves, belts, wallets, handbags, briefcases and other travelware accessories, canvas products, auto and boat covers and tops, upholstery

FEATURES

- Independently adjustable upper and lower feeding mechanism
- Horizontal axis, gear driven rotary hook
- Large bobbin
- Bobbin can be changed without removing object being sewn
- Positive walking feet
- Top and bottom feed mechanism insures even feeding of material
- Reverse stitching
- Maximum stitch length 3.2 s.p.i. (8mm)
- Also available: with Full Auto Function, model 205RBATCL(N)



SPECIFICATIONS

	205RB-1
Speed, @ Max. (S.P.M.) *	2000*
Presser Foot Lift (by Hand)	1/4" (6.5 mm)
(by Foot)	5/8" (16 mm)
Needle Bar Stroke	1-29/64" (37 mm)
Stitch Length, Max.	3.2 SPI (8 mm)
Needle	135 x 17
Bobbin Metal	24311
Pre-wound	M
Hook / Bobbin Case	24312 / 24310
Bed Size	7" x18-23/32" (178 x 475 mm)
Work Space	10-5/16" (262 mm)
Stitch Type	301


* Depending on materials, thread and operation



CLINTON INDUSTRIES

"SERVING THE SEWING INDUSTRY SINCE 1954"

Optionally available from Clinton Industries:
Automatic Footlift and Automatic Backtack



FOOTLIFT



BACKTACK