

CONSEW Since 1898**MODEL 223R-2**

With
VERTICAL AXIS ROTARY HOOK
HIGH LIFT
REVERSE FEED
SAFETY CLUTCH



223R-2
2 9/16"
DIAMETER
CYLINDER
BED

CYLINDER ARM

HIGH SPEED
CYLINDER ARM
SINGLE NEEDLE
DROP FEED NEEDLE FEED
LOCKSTITCH MACHINE

Model 223R-2

APPLICATIONS

- For sewing medium to medium-heavy weight fabrics, leather, canvas, vinyl, synthetics and various laminated and coated materials
- Designed for stitching tubular and curved work
- Suitable for sewing such products as caps, cushions, boots, shoes, auto, boat and furniture upholstery, boat covers, sails, awnings, tents, light tarpaulins, camping equipment, luggage, travelware accessories, wearing apparel, coats, etc.



FEATURES

- High lift
- Vertical axis rotary hook
- Cylinder arm
- Stitches per minute - 3000*
- Reverse stitching
- Safety clutch prevents the hook from being damaged
- Compound feed assures even feeding of several plies or slippery material

SPECIFICATIONS

Speed, Max. (S.P.M.) *	3000
Clearance Under Foot	11/32" (8.5 mm)
Needle Bar Stroke	1 5/16" (33 mm)
Stitch Length, Max.	5 s.p.i. (4.5 mm)
Needle	135 x 17
Bobbin	Metal 10656
	Pre-wound G
Hook	13086
Bed Size	2 9/16" dia x 10-9/16" (65mm dia x 268mm)
Work Space	10" (258 mm)
Stitch Type	301


* Speed depends on operation, material and thread.

Available Option:
Adjustable, spring-loaded, retractable, SWING ARM GUIDE.



CLINTON INDUSTRIES
"SERVING THE SEWING INDUSTRY SINCE 1954"

Optionally available from Clinton Industries:
Automatic Footlift and Automatic Backtack



FOOTLIFT



BACKTACK