

MODEL 228R-7DD-220V DIRECT DRIVE

With
DIRECT DRIVE
COMPUTER CONTROLLED FUNCTIONS - STITCH COUNT
AUTO THREAD-CUTTING • AUTO-LUBRICATION
AUTO-REVERSE (Back-tack)
Convenient knuckle control switches above needle.



HIGH SPEED
POST TYPE
SINGLE NEEDLE
DROP FEED
LOCKSTITCH MACHINE



Model 228R-7DD-220V

APPLICATIONS

- For sewing light to medium weight fabrics, leather, canvas, vinyl, synthetics and various coated and laminated materials
- Designed for stitching such products as wearing apparel, shoes, boots, raincoats, foundation garments, luggage, handbags, travelware accessories, leather goods, etc.
- Also used for attaching vamps and backstraps or inserting counters on heavy shoes

FEATURES

- Vertical axis hook
- Drop feed
- Roller presser foot allows for turning of sharp corners and tight curves
- Single needle
- Stitches per minute 3000*
- Reverse feed
- Automatic Footlift
- Automatic Back-tack (Reverse)
- Automatic Thread Trim
- Stitch count, multifuntion control panel

SPECIFICATIONS

Model 228R-7DD-220V

Speed, Max. (S.P.M.)		3000*
Clearance Under Foot		25/64" (10 mm)
Needle Bar Stroke		1-27/64" (36 mm)
Stitch Length, Max.		0 ~ 5 s.p.i. (5 mm)
Needle		DPX5 12 - 21#
Presser Foot Lift	by Hand	6.5 mm
	by Foot	16 mm
Post Height		7" (178 mm)
Stitch Type		301
Power		Servo Motor
Voltage		220 VAC

^{*} Speed depends on operation, material and thread.