MODEL 241-1K / 241-1TK

BUTTON SEWER



APPLICATIONS

MODEL 241-1K

- Designed to sew two and four hole buttons on light to medium material.
- Suitable for sewing snap fasteners, shank, flat and metal buttons; hooks and eyes and label tacking with use of suitable attachments. Thread severed by automatic clamp lift upon completion of sewing cycle.
- Has automatic scissor action thread trimmer with stationary and moving knife. Cutting action simultaneous with last stitch. Particularly suitable for use with heavy cotton and synthetic threads.

SPECIFICATIONS

Speed, Max. (S.P.M.)	* 1500
★ Speed is dependent on operation, material and thread.	
Needle Bar Stroke	1-59/64" (48 mm)
Number of Stitches	8-16-32 parallel stitches
Needle	175 x 7
Looper	B-372-213
Stitch Type	101

Specifications subject to change without notice.

FEATURES

- Vibrating clamp
- Single pedal operation
- Automatic clamp lift after sewing cycle
- Stitch range 8-16-32 parallel stitches - no cam changes
- Change from 2 hole to 4 hole operation by lever at operator's finger tips
- Attachments easily installed
- Interchangeable clamps for flat, shank, metal buttons, snap fasteners and label tacking
- Available as a tacker Model 241-1TK The clamp is designed for draperies, labels and basting



SINGLE NEEDLE SINGLE THREAD CHAINSTITCH CYLINDER BED

BUTTON SEWING AND TACKING MACHINES

Tray