



Models 255RB-3 / 254RB-3

WITH

LARGE BOBBIN AND VERTICAL AXIS HOOK CENTRA-LUBE®

SEMI-AUTOMATIC LUBRICATION SYSTEM

2½ S.P.I.(10mm) STITCH LENGTH

REVERSE FEED SAFETY CLUTCH



STITCH REGULATOR



Model 254RB-3
HEAVY DUTY
SINGLE NEEDLE
DROP FEED
NEEDLE FEED
LOCKSTITCH
MACHINE

Model 255RB-3

HEAVY DUTY

SINGLE NEEDLE

TRIPLE FEED:

DROP FEED, NEEDLE FEED

AND ALTERNATING

(WALKING) PRESSER FEET

LOCKSTITCH MACHINE



Models 255RB-3 / 254RB-3

Triple Feed Extra Long Stitch Drop Feed & Needle Feed

APPLICATIONS

- For sewing light to heavy-weight fabric, canvas, leather, vinyl, synthetics and various laminated and coated materials
- Designed for stitching such products as auto, boat and furniture upholstery, tarpaulins, covers, awnings, tents, umbrellas, handbags, luggage, travelware accessories, sports and camping equipment, wearing apparel, outdoor clothing, footwear, foundation garments, orthopedic appliances, etc.



255RB-3 Foot

FEATURES

- Centra-Lube[®] semi-automatic lubrication system
- Automatic hook lubrication
- Oil fed take-up
- Large bobbin and vertical axis hook
- Compound feed, walking foot mechanism assures uniform stitching
- Simple wing nut adjustment permits raising and lowering of the center foot

- Safety clutch prevents the hook from being damaged
- Safety-type handwheel
- Stitch length indicator on outside of machine
- All sizes of cording feet available
- Standard attachments easily installed
- Reverse stitching
- (255RB-3) Long Stitch 2¹/₂ SPI (10mm).

255RB-3 – Large bobbin and vertical axis hook and reverse feed and High-lift – 254RB-3 255RBL-25 – Large bobbin and vertical axis hook, reverse feed - 25" long arm – 254RBL-25 – Special order, custom made in USA, up to 30" long arm – 254RBL

SPECIFICATIONS

255RB-3

Speed, Max. (S.P.M.)			2800
Clearance Under Foot			9/16" (14mm)
Needle Bar Stroke			1-5/16" (33 mm)
Stitch Length, Max.			2-1/2 s.p.i. (10 mm)
Needle			135 x 17
Bobbin	Metal		15041
	Pre-wound		U
Hook			15040
Bed Size			7" x 18-7/8" (177 x 477 mm
Work Space			10-1/4" (258 mm)
Stitch Type			301

²⁵⁴RB-3

Speed, Max. (S.P.M.)		*	3200
Clearance Under Foot			9/16" (14mm)
Needle Bar Stroke			1-5/16" (33 mm)
Stitch Length, Max.			4 s.p.i. (5.6 mm)
Needle			135 x 17
Bobbin	Metal		15041
	Pre-wound		U
Hook			15040
Bed Size			7" x 18-7/8" (177 x 477 mm
Work Space			10-1/4" (258 mm)
Stitch Type			301

Specifications subject to change without notice.

©2007 Consew USA -307



^{*} Speed depends on thread, material and operation.