

Models **326S-1 / 326D-1 / 326DT-1**

SINGLE NEEDLE

DOUBLE NEEDLE

TANDEM
DOUBLE NEEDLE
326SH Heavy Duty
326SK-1 with Vertical Side Trimmer
Also Available: 326S-18 with 18" Long Arm

WITH

AUTOMATIC LUBRICATION SYSTEM

DIAL-TYPE STITCH LENGTH REGULATION

CAM-TYPE TAKE-UP LEVER

HINGED PRESSER FOOT



326S-1

HIGH SPEED
SINGLE NEEDLE, TANDEM OR TWO NEEDLE
DROP FEED
DOUBLE CHAINSTITCH MACHINE

Models 326S-1 / 326D-1 / 326DT-1 / 326SH / 326SK-1/ 326S-18

Single Needle

Double Needle

Tandem Double Needle

Heavy Duty

Side Trimmer

Long Arm

APPLICATIONS

- For sewing light to medium weight fabrics, knits and denim
- Suitable for such operations as lap seam felling, hemming, binding, joining and plain stitching
- Designed for sewing stretchable seams
- For stitching such products as blouses, shirts, suits, knitted goods, ladies and children's dresses and skirts, coats, pants, uniforms, pajamas, work clothes, etc.

FEATURES

- Automatic lubrication
 - Dial-type stitch length regulation
 - Cam-type take-up lever minimizes tension on the lower threads to allow stitches to stretch
 - Stitches per minute - 5000 *
 - Moving presser foot eliminates slippage and puckering
-
- Also available as two needle - four thread double chainstitch – models 326D and 326DT tandem and model 326SK (*with vertical side trimmer*) and model 326S-18 (*with 18" long arm*)
-



SPECIFICATIONS

Speed, Max. (S.P.M.) *	5000	Bed Size	7" x 18-7/8" (178 x 478 mm)
* Depending on material, thread and operation.		Work Space	10" (258 mm)
Clearance Under Foot	5/16" (8 mm)	Stitch Type	401
Needle Bar Stroke	1-3/16" (30 mm)	Two Needle Needle Distances	1/4" standard
Stitch Length, Max.	5-1/2 s.p.i. (4.7 mm)		1/8"-1/2" on request
Needle	149 x 7		5/16" and 3/8" on request