

CONSEW Since 1898

Model 327RB-2


TWO NEEDLE

Also available: Model 327RBL-25

WITH

**CENTRA-LUBE® SEMI-AUTOMATIC LUBRICATION
SYSTEM**

**LARGE VERTICAL AXIS HOOKS AND BOBBINS
DISENGAGEABLE RIGHT AND LEFT NEEDLE BARS
REVERSE FEED**




327RB-2
needle
and
foot
closeup
showing
the split
needle bar



FLAT BED

**Double Needle
Split Bar**



ANGULAR STITCHING

**HIGH SPEED
TWO NEEDLE
ANGULAR STITCHING
(SPLIT NEEDLE BAR)
DROP FEED, NEEDLE FEED
LOCKSTITCH MACHINE**

MODEL 327RB-2

Also available: Model 327RBL-25

APPLICATIONS

- For medium to heavy duty materials such as cloth, leather, canvas, vinyls, synthetics and various coated and laminated materials
- Designed for sewing operations which require decorative or functional. angular stitching such as collars, lapels, pocket flaps, pockets and fly fronts
- Used for stitching such products as wearing apparel, table cloths, brassieres and leather accessories
- General parallel / two-needle stitching (top or run stitching)



FEATURES

- The compound feed mechanism assures perfect and uniform stitching and eliminates slippage
- Large hooks and bobbins.
- Special bobbin case cap eliminates loose bottom stitches when angular stitching is employed
- Easy operation of disengageable right and left needle bars by use of finger-touch lever
- Centra-Lube® semi-automatic lubrication system
- Automatic hook lubrication
- Oil fed take-up
- Reverse stitching
- Large range of gauge sets available
- Safety clutch protects the hooks from being damaged

SPECIFICATIONS


Speed, Max. (S.P.M.)*	2200	
Clearance Under Foot	⁹ / ₃₂ " (7 mm)	
Needle Bar Stroke	1 1/4" (32 mm)	
Stitch Length, Max.	4 1/2 s. p. i. (5.5 mm)	
Needle	135 x 7	
Bobbin	Metal	16408
	Pre-wound	U
Hook	16407	
Work Space	10" (258 mm)	
Bed Size	7" x 20 3/8" (177 x 518 mm)	
Needle Distances	1/4" Standard (1/8-1 1/4" avail)	
Stitch Type	301	

* Speed depends on operation, material and thread.



CLINTON INDUSTRIES
"SERVING THE SEWING INDUSTRY SINCE 1954"

Optionally available
from Clinton Industries:
Automatic Footlift and
Automatic Backtack



FOOTLIFT



BACKTACK

Available Option: Adjustable, spring-loaded, retractable, SWING ARM GUIDE. (Works on both 1 or 2 needle machines.)

