

Models 3301/3302/3303/3304/3305/3306

PULLER DEVICE AVAILABLE

ALSO AVAILABLE: 3400 SERIES CYLINDER BED MACHINES

WITH

SEMI-AUTOMATIC LUBRICATION SIMPLIFIED LOOPER THROW-OUT







available as a special order

HIGH SPEED DROP FEED, NEEDLE FEED (COMPOUND FEED)

DOUBLE CHAINSTITCH MACHINES

1-2-3-4-5-6 NEEDLE VERSIONS



Models 3301/3302/3303/3304/3305/3306

APPLICATIONS

- For sewing medium to heavy weight fabrics such as vinyl, leather, canvas, denim, synthetics and various coated and laminated materials
- Suitable, for stitching operations on such products as awnings, tents, tarpaulins, auto, marine and furniture- upholstery, auto interiors, auto tops, handbags, luggage, belts, curtains, draperies, bed spreads, blankets, bathing trunks, boxer shorts, trousers, uniforms, walking shorts, jackets, work clothes, slippers, women's shoes, canvas shoes, sports equipment, carpets, mattresses, mattress pads, gloves and numerous other articles
- Machines can be used for seaming, binding, welting, banding, bibbing, lap seam felling and taping with appropriate attachments

FEATURES

- Semi-automatic lubrication with recirculating pump
- Simplified looper throw-out
- Easy accessibility for threading loopers
- Compound feed mechanism ensures even feeding of article being sewn
- No bobbin winding or changing (double chainstitch)
- Attachments easily installed
- Stitches per minute –4000*
- Special order up to 25" long arm







NUMBER of NEEDLES	MODEL	MODEL with Puller
Single	3301	3301P
Two	3302	3302P
Three	3303	3303P
Four	3304	3304P
Five	3305	3305P
Six	3306	3306P





Optionally available from Clinton Industries: Automatic Foot Lift and Automatic Puller Lift

SPECIFICATIONS

Speed, Max. (S.P.M.) * Without Puller With Puller	4000 3000	
Clearance Under Foot	⁵ / ₁₆ " (8mm)	
Needle Bar Stroke	1- ¹¹ /32" (34 mm)	
Stitch Length, Max.	3 s.p.i. (8.5 mm)	
Needle	62 x 59	
* Speed depends on thread, material and operation.		

Looper	20301
Bed Size	7" x 20- ³ / ₈ " (177 x 518 mm)
Work Space	10- ⁵ / ₈ " (270 mm)
Needle Distances	³ / ₁₆ " (4.7 mm) – 2" (50.8 mm)
Stitch Type	401

