

CONSEW Since 1898**Model 345-3****Model 345-3P with Cloth Puller****FEED OFF THE ARM**

WITH
FULLY AUTOMATIC LUBRICATION
CHAIN CUTTER
SCREW ADJUST STITCH REGULATOR



Model 345-3

HIGH SPEED
FEED-OFF-THE-ARM TYPE
DROP FEED
DOUBLE CHAINSTITCH
LAP SEAM FELLING MACHINE
3 NEEDLES

Model 345-3

APPLICATIONS

- For sewing light to heavy weight materials
- Suitable for stitching shirts, sleep-wear, jeans, pants, skirts, uniforms, heavy overalls, raincoats and other similar products
- Designed for any lap seam felling operation including difficult-to-sew tubular products

FEATURES

- Fully automatic lubrication
- Chain cutter
- Cylinder arm allows for lap seam felling on narrow openings
- Presserbar lift – can be controlled by knee lifter or foot pedal
- Screw adjust stitch regulator

Number of Needles	Model	Model With Puller
Three	345-3	345-3P



SPECIFICATIONS

	345-3	345-3P
Speed, Max. (S.P.M.)	3600 *	3600 *
Clearance Under Foot	5/16" (8 mm)	5/16" (8 mm)
Needle Bar Stroke	1 5/16" (33.4 mm)	1 3/8" (35 mm)
Stitch Length, Max.	6 s.p.i. (4 mm)	6 s.p.i. (4 mm)
Needle	149 x 5	149 x 5
Cylinder Diameter at Needle Bar	1 23/32" (53.5 mm)	1 23/32" (53.5 mm)
Clearance to Right of Needle Bar	8" (203 mm)	8" (203 mm)
Needle Distances	2 Needle 3/16" (4.8 mm)	3/16" (4.8 mm)
	1/4" (6.4 mm)	1/4" (6.4 mm)
3 Needle	1/8" x 1/8" (6.4 mm)	1/8" x 1/8" (6.4 mm)
Stitch Type	401	401

* Speed depends on thread, material, set-up and operation.