

Since 1898
CONSEW®

MODEL 345-3

Model 345-3P with Cloth Puller

WITH
CHAIN CUTTER
SCREW ADJUST STITCH REGULATOR



Model 345-3

HIGH SPEED
FEED-OFF-THE-ARM TYPE
DROP FEED
DOUBLE CHAINSTITCH
LAP SEAM FELLING MACHINE
3 NEEDLES

Model 345-3

APPLICATIONS

- For sewing light to heavy weight materials
- Suitable for stitching shirts, sleep-wear, jeans, pants, skirts, uniforms, heavy overalls, raincoats and other similar products
- Designed for any lap seam felling operation including difficult-to-sew tubular products

FEATURES

- Chain cutter
- Cylinder arm allows for lap seam felling on narrow openings
- Presser bar lift – can be controlled by knee lifter or foot pedal
- Screw adjust stitch regulator


Three Needles: Model 345-3 / Model 345-3P is with Puller



Detail View of 345-3



Detail View of 345-3



Stitching

Stitching



This detail shows the 3 needles and sewing area.

SPECIFICATIONS

	345-3	345-3P
Speed, Max. (S.P.M.)	3600 *	3600 *
Clearance Under Foot	5/16" (8 mm)	5/16" (8 mm)
Needle Bar Stroke	1 5/16" (33.4 mm)	1 3/8" (35 mm)
Stitch Length, Max.	6 s.p.i. (4.2 mm)	6 s.p.i. (4.2 mm)
Needle	149 x 5	149 x 5
Cylinder Diameter at Needle Bar	123/32" (53.5 mm)	123/32" (53.5 mm)
Clearance to Right of Needle Bar	8" (203 mm)	8" (203 mm)
Needle Distances	2 Needle 3/16" (4.8 mm)	2 Needle 3/16" (4.8 mm)
	3 Needle 1/4" (6.4 mm)	3 Needle 1/4" (6.4 mm)
Stitch Type	7/64 x 7/64 (5.6mm total), 1/8 x 1/8 (6.4mm), 5/32 x 5/32 (8.0mm), 3/16 x 3/16 (9.6mm)	7/64 x 7/64 (5.6mm total), 1/8 x 1/8 (6.4mm), 5/32 x 5/32 (8.0mm), 3/16 x 3/16 (9.6mm)
	401	401

*Speed depends on thread, material, set-up and operation.



Convenient glass viewer for checking oil level.