

Model 387RB-2

WITH CENTRA-LUBE®

Also available 384RB-2 (needle feed)

SEMI-AUTOMATIC LUBRICATION SYSTEM

LARGE VERTICAL AXIS ROTARY HOOKS AND BOBBINS

REVERSE FEED

SAFETY CLUTCH



TWO NEEDLE DROP FEED, NEEDLE FEED **WALKING FOOT ALTERNATING PRESSER FEET** LOCKSTITCH MACHINE



Model 387RB-2

Also available 384RB-2 (needle feed)

APPLICATIONS

- For sewing light to heavy-weight fabrics, leather, vinyl, upholstery, synthetics, canvas and various coated and laminated materials
- Designed for stitching tubular and curved work.

 Suitable for sewing such products as caps, cushions, boots, shoes, auto, boat and furniture upholstery, tarpaulins, covers, sails, tents, awnings, umbrellas, tops, bags, luggage, handbags, travelware accessories, sports and camping equipment, wearing apparel, orthopedic appliances, slippers, filters, etc.

FEATURES

- Two needle mechanism readily makes two parallel lines of stitches
- Large vertical axis rotary hooks and bobbins assure longer operation between bobbin changes
- Compound feed, walking foot mechanism assures even feeding of several plies or of slippery materials Centra-Lube® semi-automatic lubrication system
- Reverse feed
- Safety clutch prevents the hook from being damaged
- Simple adjustment permits the raising and lowering of the center foot which allows for sewing of different thicknesses of material
- Various needle gauges available

SPECIFICATIONS

Speed, Max. (S.P.M.)*		2500*		
Clearance Under Foot		11/32"	11/ ₃₂ " (8.5mm)	
Needle Bar Stroke		1 ⁵ /16"	(33.2mm)	
Stitch Length, Max.		@4 s.p.	i. (6.2 mm)	
Bobbin	Metal	15	15041	
	Pre-wound		S	
Hook	13719			
Bed Size	3	3 ⁷ / ₃₂ " dia. x 13"	(82mmØ x 330mm)	
Work Space		10" (254 mm)		
Stitch Type		301		
Needle		135 x 17		
Standard Needle Spacings: 1/8", 1/4", 3/8", 1/2"				

^{*} Speed depends on materials, thread and operation.







Optionally available from Clinton Industries: Automatic Footlift and Automatic Backtack



