

WITH
 VERTICAL AXIS ROTARY HOOKS
 INTERMITTENT WHEEL FEED
 INTERMITTENT POSITIVELY DRIVEN
 ROLLER PRESSER
 SIMPLIFIED SEMI-AUTOMATIC LUBRICATION
 ANTI-FRICTION BALL AND ROLLER BEARINGS
 BUILT-IN BOBBIN WINDER

Models 701 / 702 701LP - Left Post



Model 701
 Single Needle



Model 702
 Two Needle



Model 701LP
 Single Needle
 Left Post

HIGH SPEED
 SINGLE AND
 TWO-NEEDLE
 POST BED
 LOCKSTITCH
 MACHINES

TOP AND BOTTOM
 DRIVEN ROLLER FEED
 POSITIVELY DRIVEN
 ROLLER PRESSER

POST BED

Models 701 / 702 and 701LP- Left Post

APPLICATIONS

- Lower and driven presser wheel feeding action combined with needle feed provide powerful transport for slippery materials of any type as well as leather, vinyl and polyethylene plastics, oil cloth, just any material difficult to feed, coated and laminated fabrics.
- Suitable for stitching hollow, tubular and curved articles and climbing over thick sections always assuring constant stitch length.

FEATURES

- As many as 29 anti-friction ball and needle roller bearings (depending on model) for easy maintenance.
- Continuous lubrication from copious reservoir.
- Vertical axis rotating hooks.
- Triple feeding mechanism assures even feeding of difficult-to-sew materials.

AVAILABLE MODELS

- 701** - Single needle, lower wheel feed, driven upper wheel feed, needle feed
- 702** - Two needle, all other features same as Model 701
- 701LP** - Left hand post
- 701U** - Same as basic model, modified for maximum stitch length up to 21/64 (8mm)
- 701X** - Same as basic model, modified for very heavy thread
- 701UX** - Same as basic model, modified for maximum stitch length and heavy thread
- 701ATCL** - Fitted with automatic thread trimmer and presser lift
- 702ATCL** - Fitted with automatic thread trimmer and presser lift

SPECIFICATIONS


	Model 701	Model 702
Speed, Max. (S.P.M.)*	3500	
Clearance Under Foot	9/32" (7mm)	
Needle Bar Stroke	1 1/2" (38mm)	
Stitch Length, Max. (s.p.i.) 5 (5 mm)		6 (4 mm)
Needle	135 x 7 (cat. 1955)	
Bobbin	Metal	38033
	Pre-wound	G
Hook	38032	
Bed Size	7" x 20 3/8" (177 x 518 mm)	
Work Surface	2" x 21 3/32" (52 x 61mm)	2" x 31 3/16" (52 x 97mm)
Post Height	7" (178mm)	
Stitch Type	301	
Needle Gauge		Standard 1/16" (1.6 mm)
Needle Gauges Available		1/32" to 3/16" (0.8 to 4.8mm)

* Speed dependent on materials, thread and operation.

Specifications subject to change without notice.

web: www.consew.com

©2023 Consew USA -0123




Closeup of 701LP Post and Needle

Available Option:
Adjustable, spring-loaded, retractable, SWING ARM GUIDE.



CLINTON INDUSTRIES
"SERVING THE SEWING INDUSTRY SINCE 1954"

Optionally available from Clinton Industries:
Automatic Footlift and Automatic Backtack



FOOTLIFT



BACKTACK