

CONSEW Since 1898


Model 733R-5

(Replaces Models 733R-2 and 733R-4)

Model 733R-25 Longarm

Models 733R-5AL(N) / 733R-25AL(N) with air powered footlift

WITH
EXTRA LARGE, LONG-BEAK
OSCILLATING SHUTTLE HOOK AND BOBBIN
EXTRA HIGH FOOT LIFT- (1 1/4")
TWO ROW FEEDER
REVERSE FEED



Detail of 733R-5 showing the two row feeder and the 1-1/4" extra high foot lift



Model 733R-25

With 25" of workspace

EXTRA HEAVY DUTY
LONG ARM
SINGLE NEEDLE
DROP FEED
ALTERNATING
PRESSER FEET
LOCKSTITCH MACHINE

Models 733R-5 / 733R-25

Models 733R-5AL(N)/733R-25AL(N) with air powered footlift

APPLICATIONS


- For stitching extra heavy-weight materials
- Designed for such operations and products as safety and logging belts, cargo slings, buffing wheels, tents, sails, harnesses, tarpaulins and covers, fabric structures, construction barriers, parachutes, balloons, industrial bags, boot stitching, book binding

FEATURES

- Synchronized upper and lower feeding mechanism assures uniform stitching
- Alternating presser feet
- Steel insert for take-up hinge
- Reverse stitching - hand or foot operated
- Stitch regulator - hand or foot operated
- Presser foot lift - hand or foot operated
- 1 1/4 inch presser foot lift
- Two row feeder
- Two stitches to the inch
- Stitches per minute - 550
- Extra large, long-beak oscilating shuttle, hook and bobbin
- Belt guard




TENTS




PARACHUTE HARNESSES



733R-5AL(N):
rear view showing Air Foot Lift mechanism



SEAT BELTS



BUFFING WHEELS

SPECIFICATIONS

Speed, Max. (S.P.M.)*	550	Hook	35224
Clearance Under Foot	1 1/4" (31.8 mm)	Bed Size	10" x 26 1/4" (258 x 655 mm)
Needle Bar Stroke	2 3/32" (53 mm)	Work Space	16 1/4" (413 mm)
Stitch Length, Max.	2 s.p.i. (13 mm)	Stitch Type	301
Needle	1000 or 1000H	Weight	231 lbs. (105 kg.)
Bobbin	Metal	733R-25 Work Space: 25" (640 mm)	
	Pre-wound		
	35226		
	41		

* Speed depends on operation, materials and thread