

Model 757R-3 Model 757R

WITH

LARGE OSCILLATING SHUTTLE HOOK REVERSE FEED **BUILT-IN BOBBIN WINDER** CAM TAKE-UP LEVER **HEAVY BALANCE WHEEL** WORK SPACE - 161/2" (420mm)







WORK SPACE - 153/4" EXTRA HIGH - 1" (25.4 mm) FOOT LIFT

EXTRA HEAVY DUTY LONG ARM SINGLE NEEDLE LOCKSTITCH MACHINE




Models 757R-3 / 757R

APPLICATIONS

- Suitable for sewing heavyweight materials such as canvas, vinyl, leather, synthetics and various coated, laminated and rubberized fabrics.
- Appropriate for use in upholstery, footwear, leather, canvas industries.
- Designed for stitching such products as tents, sails, harnesses, tarpaulins, safety belts, parachutes, balloons, industrial bags, boots, book bindings; auto, boat and furniture upholstery, sports and camping equipment, orthopedic appliances, suitcases, knapsacks, and outerwear made of extra heavy duty materials.
- Designed for extra thick threads.

7R






FEATURES

- Large oscillating shuttle hook
- Work space 16½" (420mm)
- Reverse feed
- Built-in bobbin winder
- Cam take-up lever
- Extra high presser lift for sewing extra heavy materials
- Heavy balance wheel
- Triple Transport (walking foot): Bottom, top and needle feed.

CLINTON INDUSTRIES "SERVING THE SEVING INDUSTRY SINCE 1954"

Optionally available from Clinton Industries: Automatic Footlift and Automatic Backtack





FOOTLIFT

BACKTACK

SPECIFICATIONS

Model 757R-3

Speed, Max. (S.P.M.)	800*
Presser Lift	13/16" (20mm)
Needle Bar Stroke	2 ¹³ / ₆₄ " (56mm)
Stitch Length, Max.	1.7 s.p.i. (15mm)
Needle	7 x 3
Bed Size	26" x 9 7/8" (660 x 251 mm)
Work Space	16½" (420 mm)
Stitch Type	301

^{*} Speed dependent on materials, thread and operation

Model 757R

Speed, Max. (S.P.M.)		1200*
Presser Lift		1" (25.4mm)
Needle Bar Stroke		213/ ₆₄ " (56mm)
Stitch L	ength, Max.	21/2 s.p.i. (10mm)
Bobbin	Metal	28092
	Prewound	33
Needle		7 x 3
Shuttle	Hook	28091C
Bed Siz	ze	26" x 9 ⁷ / ₈ " (660 x 251 mm)
Work S	pace	15 ³ / ₄ " (400 mm)