

CONSEW® Since 1898

with

SKIP AND NON-SKIP STITCH LEVER
ADJUSTABLE THREAD TENSION
1 to 1 NON-SKIP STITCH AND
2 to 1 SKIP STITCH

Plus...

Stitch penetration and stitch length adjustment dials give you big-machine features in a light-weight, compact and fully portable unit

Model 75T

ALL PURPOSE, PORTABLE,
SINGLE THREAD, CHAINSTITCH,
BLINDSTITCH MACHINE

Standard
110V. Motor
Included

Motor mounted
on rear of
machine

Featuring
SWING-DOWN
CYLINDER ARM
with
METAL SWING
PLATE



Knee-Lifter
included

Electronic foot
controller included




Table
clamp
included



SPECIFICATIONS

Speed, Max. (S.P.M.)	1000 *
Stitch Length, Max.	3 1/2 s.p.i. (7mm)
Needle Style	LWX 6T
Looper	471
Cylinder Diameter	1 5/8" (40 mm)
Work Space (Needle to Arm)	4" (100 mm)
Stitch Type	103

* Speed depends on materials, operation and thread

Ideal for alteration rooms, tailors, clothing rentals, dry cleaners, department stores, dressmakers and home use

Perfect for sewing all weights of materials including synthetics, woolsens, cottons, fabrics and knits

1 to 1 non-skip stitches, typical operations include felling edge tapes, bottoms of trousers, cuffs, wiggling in sleeves, facings to canvas and knit goods, turned-up bottoms of fully lined coats, padding collars and lapels, and reinforcing trouser seats

2 to 1 skip stitch for hemming dresses, skirts, slacks, trousers, sportswear, ladies coats, draperies, blouses and other articles

Suitable for felling operations requiring a skip stitch to simulate hand-stitching

2 to 1 skip stitch is recommended for synthetics and other lightweight materials and 1 to 1 for heavier cotton, woolen and linen goods

BLINDSTITCH