



Since 1898
CONSEW[®]

Model 767RB-Series

HEAVY DUTY
WALKING FOOT
FULL FUNCTIONS PLUS
DROP FEED, NEEDLE FEED
AND ALTERNATING
PRESSER FEET
LOCKSTITCH MACHINES


767RB/26 1 NEEDLE
M BOBBIN

767RB/32 1 NEEDLE
U BOBBIN

Comes in 220v only
110-220v converter option is available



767RB/32



Heavy Duty Stitching

WITH
LARGE DROP-IN BOBBIN
AUTO REVERSE FEED
AUTO FOOT LIFT
AUTO TREAD TRIM
NEEDLE POSITIONER




CONSEW® 767RB Series

APPLICATIONS

- For wide range of industries for all types of medium/heavy duty applications. Such as: Automotive, Upholstery. Marine, Tie-down and Sling, Harness, Parachute, Tents and Awnings, Apparel, Bedding, etc.

ADDITIONAL FEATURES

- Direct Drive
- Advanced Oiling System
- 13.6" Arm Length with 5.1" Vertical Clearance
- Presser Foot Clearance up to 16mm.
- High needle bar stroke
- Convenient one-button high step
- Full Auto-functions including: Auto trimmer, auto reverse, auto footlift, climbing device, needle positioner, stitch counting, line tacking, and pattern stitching.
- External compressed air source required (40 - 50 psi)
- Bobbin winder built-in
- Adjustable parameter settings
- Convenient knuckle switches on arm: Reverse, Auto back-tack pause, High step.
- Safety clutch
- Power: 220v single phase
- Automatic programmable beginning and ending Backtacking
- LED under lighting built in
- Hi-quality metal bearings for hi-speed and long production runs



SPECIFICATIONS

Speed - s.p.m.	3000 spm*
Max. Stitch Length	9 mm
Manual Presser Foot Lift	9 mm
Pneumatic Foot Lift	16 mm maximum
Bobbins	26 mm (M) and 32 mm (U)

Number of Needles	1
Needle System	134 -35
Air Pressure Required	40 - 50 psi
Workspace	13.6" x 5.51" (345 x 140mm)

* Speed depends on thread, material and operation.