



Models CN897VF and CN897VC

CN897VFB-1 and CN897VCB-1 for Binding Attachments

V-SERIES HIGH SPEED COVERSTITCH MACHINES


WITH
 FULLY AUTOMATIC LUBRICATION
 DIFFERENTIAL FEED with MICROMETRIC ADJUSTMENT
 PUSHBUTTON STITCH REGULATOR
 THREAD LUBRICATING AND NEEDLE COOLING SYSTEM



Model CN897VC
CYLINDER-BED
VERSION



Model CN897VF
FLAT-BED VERSION



TWO NEEDLE — 4 THREAD
 THREE NEEDLE — 5 THREAD
 FLAT-BED AND CYLINDER-BED
 for PLAIN SEAMING

BOTTOM HEMMING and ELASTIC ATTACHING

Models CN897VF and CN897VC / CN897BVF and CN897BVC

APPLICATIONS

- For sewing light to heavy-weight materials.
- Model CN897VF – Flat-bed for general seaming
- Model CN897VC – Cylinder-bed for general seaming
- Both models suitable for hemming, tape binding, elastic inserting, etc.



FEATURES

- Speed, Max. up to 6000 s.p.m.*
- Push-button stitch regulator
- External cooling of oil supply
- Fully automatic lubrication with visual flow controls
- Lubricating oil continuously filtered by replaceable filter
- Differential feed with micrometric adjustment for shirring and stretching. Ratio up to 4 to 1.
- Intermittent action possible
- Standard type UY128GAS needles
- Silicone based needle cooling and thread lubricating

AVAILABLE OPTIONS

- UTA • Under thread trimming device (pneumatic)
- ST • Top cover thread trimming device
- UTM • Under thread trimming device (electric)
- W • Thread wiper (electric)
- EC • Tape Cutter (electric)



CLINTON INDUSTRIES
SERVING THE SEWING INDUSTRY SINCE 1954

Optional Automation Upgrades available from Clinton Industries:

- Tape Cutting Device
- Thread Trimmers

CONFIGURATIONS

MODEL	NEEDLES	LOOPERS	THREADS
CN897VF	2	2	4
CN897VF	3	2	5
CN897VC	2	2	4
CN897VC	3	2	5

Note: Removing a needle allows for different widths of cover stitch and bottom cover only




SPECIFICATIONS

MODEL CN897VC

MAX. SEWING SPEED: 6,000 S.P.M.
LIFT OF PRESSER FOOT: 7.0 mm
DIFFERENTIAL RATIO: 1 : 0.3 ~ 1 : 2.9
STANDARD NEEDLE GA.: Comes with 3-needle, 5.6 mm
(Optional Needle Gauges available)
2 Needles: 3.2, 4.0, 4.8, 5.6, 6.4 mm
3 Needles: 5.6, 6.4 mm
STITCH LENGTH: 1.4 ~ 3.6 mm
NEEDLE BAR STROKE: 31 mm
NEEDLE SYSTEM: UY128GAS

MODEL CN897VF

MAX. SEWING SPEED: 6,000 S.P.M.
LIFT OF PRESSER FOOT: 7.0 mm
DIFFERENTIAL RATIO: 1 : 0.7 ~ 1 : 2.0
STANDARD NEEDLE GA.: Comes with 3-needle, 5.6 mm
(Optional Needle Gauges available)
2 Needles: 3.2, 4.0, 4.8, 5.6, 6.4 mm
3 Needles: 5.6, 6.4 mm
STITCH LENGTH: 1.4 ~ 3.6 mm
NEEDLE BAR STROKE: 31 mm
NEEDLE SYSTEM: UY128GAS



CN897VF needles closeup

* Speed depends on operation, materials and thread