



PREMIER® P1541S-CC

Drop Feed, Needle Feed Walking Foot Lockstitch Machine

Adjustable climbing device



- Large Horizontal Automatically Oiled Hook
- Needle Frame Stabilizer
- Barrel-type Slip Bearing Safety Clutch
- High Needle Bar Stroke
- High Presser Foot Lift
- Quick Release Knee Presser Pedal
- Easy dial-adjustable stitch regulator
- Reverse
- Large Side-Loaded Bobbin
- Built-In Bobbin Winder
- Built-In Synchronizer Hub
- Improved feeding motion for all thicknesses of materials without gathering
- Adjustable Climbing Device
- Adjustable Take-Up Guide for thread loop timing
- Lower thread guide with tension
- Large Hand Wheel







Built-In Synchronizer Hub

SPECIFICATIONS		
Speed, Max. (S.P.M.)		2800*
Presser Foot Lift	By Hand	²³ / ₆₄ " (9 mm)
	By Knee	⁵ /8" (16 mm)
Needle Bar Stroke		1- ²⁷ / ₆₄ " (36 mm)
Stitch Length, Max.		2.8 s.p.i. (9 mm)
Needle		135 x 17
Hook	Large Lubricating Hook	
Work Space	10 ¹ / ₄ " x 3- ¹⁵ / ₁₆ " (260 x 100 mm)	
Stitch Type	301	

^{*} Speed depends on thread, material and operation.